

PAT-NO: JP408237058A
DOCUMENT-IDENTIFIER: JP 08237058 A
TITLE: SURFACE ACOUSTIC WAVE DEVICE AND ITS FREQUENCY
CHARACTERISTIC ADJUSTMENT METHOD
PUBN-DATE: September 13, 1996

INVENTOR-INFORMATION:
NAME
UU, HOKUHOA

ASSIGNEE-INFORMATION:
NAME COUNTRY
OKI ELECTRIC IND CO LTD N/A

APPL-NO: JP07038651
APPL-DATE: February 27, 1995

INT-CL (IPC): H03H003/10, H03H009/145 , H03H009/25

ABSTRACT:

PURPOSE: To set the center frequency of a surface acoustic wave device to a desired frequency.

CONSTITUTION: An insulating film 20 and a ferromagnetic thin film 21 are formed on a interdigital transducer IDT 15 on a piezoelectric substrate 11. The piezoelectric substrate 11 is mounted on, e.g. a ferromagnetic stem and a static magnetic field is applied to the piezoelectric substrate 11 in the vertical direction. The ferromagnetic thin film 21 and the stem are magnetized permanently by a static magnetic field and the surface pressure of the piezoelectric substrate 11 is increased by the magnetic attractive force. Since the film 21 and the stem are magnetized permanently, the

magnetic
attractive force is left between the ferromagnetic thin film 21 and
the stem
even when they are released from the static magnetic field and the
surface
pressure of the piezoelectric substrate 11 is adjusted constant at
all times.
The propagation speed of the surface acoustic wave is changed by the
increase
in the surface pressure to obtain a desired center frequency.

COPYRIGHT: (C)1996,JPO